BUBLIING L

TECHNICAL SPECIFICATIONS





All the answers, in one place.

It stands out for its versatility.

It offers a quiet space for small group meetings, with functional furniture and support materials for presentations or strategic planning.

- A space for 4 people.
- III Class A soundproofing.
- Guaranteed privacy and comfort.
- \lessapprox Automatic ventilation and lighting.
- 🖒 Designed for PRM.

1

BUBLIING L | TECHNICAL SPECIFICATIONS

GENERAL DESCRIPTION

Dimensions Exterior: 2356x1456x2245 mm / 92,76x57,32x88,39 in.

With Bubliing Fresh Air: +50 mm / 1,97 in.

Interior: 2058x1426x2114 mm / 81,09x56,14x83,23 in.

Entry Height: 23 mm / 0,91 in. **Door:** 2134x949 mm / 83,90x37,36 in.

Standard weight 740 kg / 1632 lb.

Acoustics Class A | dB,A > 30 dB.

Guaranteed speech level reduction according to ISO 23351-1 testing

method, with one of the highest ratings in the industry.

Fan flow rate Airflow: 1121,6 m³/h (8 fans).

Air is renewed, on average, every 5.6 minutes.

Airflow can be manually adjusted.

In standby mode, the system activates for 10 minutes per hour.

Lighting Ceiling Light: LED lighting with a color temperature of

 $3500\mbox{K}-4000\mbox{K},$ providing up to 500 lux on the desk. Lighting is automatic and can be manually adjusted.

Occupancy indicators LED sensor technology with exterior red or green light.


Digital control 7" touchscreen digital control panel.

Mobility High-resistance leveling feet adjustable from inside the booth.

BUBLIING is designed to accommodate people with reduced

mobility and wheelchair users.

Ramp with an entry height of 23 mm / 0.91 in.



MATERIALS

Exterior Exterior panels: Made of powder-coated steel, available in 10

interchangeable colors.

Frame and door: Made of matte black lacquered aluminum (RAL

9005) with concealed pivot hinge. Handle: Made of textured black polymer. Glass: 8 mm / 0.31 in clear acoustic glass.

Interior Structure: Metal frame, wood, and recycled acoustic foam.

Covering: 100% polyester fabric available in 12 colors. **Flooring:** 100% polyamide carpet available in 4 colors.

Table: Birch plywood top with white, black fingerprint-resistant

thermolaminate, or wood imitation finish.

Metal support structure.

Standard furniture Table Dimensions: 1195x830x730 mm / 47,05x32,68x28,74 in.

Table Height: 730 ou 1050 mm / 28,74 ou 41,34 in. Maximum load for the table is 50 kg / 110.23 lbs.

Sofa Dimensions: 1173x570x810 mm / 46,18x22,44x31,89 in. Sofa upholstered in 100% polyester fabric, available in 12 colors.


Maximum load for the sea is 135 kg / 297.12 lbs.


Clothes hangers (2): lacquered in textured black RAL 9005.

PRM kit This model is designed to meet the needs of people with reduced

mobility (PRM). Please refer to the PRM kit technical sheet for

additional details.





BUBLIING L | TECHNICAL SPECIFICATIONS

SAFETY

products are tested and classified according to national or

international standards.

Fabrics: EN 13501-1 Adhered Class B, s1, d0.

Foams: ISO 3795. Carpet: EN 13501-1 Cfl – s1. Wood: EN 13986, Class D-s2, d0.

Seismic protection The BUBLIING can be supplied with a system that allows attachment

to the floor, available for seismic regions.

ENERGY

Charger output 2x Schuko sockets - 230 V.

1x USB-C port. 1x USB-A port.

Optional: RJ45 Network socket; HDMI input.

Equipment power 93 W.

Standby consumption 0,74 W.

Standard consumption AC output (electrical socket); 100-240 VAC, 16 A, 50-60 Hz.

Electrical equipment 65 W USB-C output.

EXTRA FEATURES

Options Metal hydraulic air spring for door closer.

Bubliing Fresh Air system, non-adjustable and noise-free.

Sofa cushion upholstered in 100% polyester fabric, available in 12 colours. Metal **interior monitor stand** with VESA mounting. Monitor not included.

Maximum monitor size is 13-42 inches.

 $\label{thm:monitor stand} \textit{Metal exterior monitor stand with VESA mounting.} \ \textit{Monitor not included}.$

Maximum monitor size is 37-70 inches.

Outdoor whiteboard 1040x910 mm / 40.94x35.83 in.

SPACE AND INSTALLATION

Required Space BUBLIING depth 1456 mm / 57.32 in + Door opening of 100°.

Minimum recommended airflow space above and on the sides: 150


mm / 5.91 in.

Installation Space Installation requires 500 mm / 19.69 in of free space around the

BUBLIING.

Assembly Assembly time: 2 hours.

Number of people: 3 people.



BUBLIING L | STANDARD FURNITURE





LOW TABLE 1195x830x730 mm. 47,05x32,68x28,74 in.



SOFAS 1173x570x810 mm. 46,18x22,44x31,89 in.



CLOTHES HANGERS 2 units.

$\textbf{BUBLIING} \; \textbf{L} \; | \; \textbf{OPTIONAL} \; \textbf{FURNITURE}$





HIGH STOOL 1195x830x1050 mm. 47,05x32,68x41,34 in.

BUBLIING L | STANDARD FEATURES



CONNECTIVITY

2x Schuko sockets - 230 V.

1x USB-C port.

1x USB-A port.



CONTROL SCREEN
7-inch digital control.



OCCUPANCY INDICATOR
Exterior LED sensor technology.
2 units.

BUBLIING L | OPTIONAL FEATURES



AIR SPRING
Metal hydraulic system for the door.



BUBLIING FRESH AIR Non-adjustable system. Noise-free.



SOFA CUSHION Covered with 100% polyester fabric. 12 colors available.



INDOOR MONITOR STAND Monitor not included. Size: 13-42 inches.



OUTDOOR MONITOR STAND Monitor not included. Size: 37-70 inches.



OUTDOOR WHITEBOARD 1040x910 mm. 40,94x35,83 in.



BUBLIING L | FINISHES



TABLE TOP



Due to the different monitor and printer configurations, the appearance of the finishes may vary from the actual finish. To ensure that the chosen finishes meet your expectations, please refer to physical samples or contact a BUBLIING representative.

WORK WELL, LIVE BETTER
WITH **BUBLIING L**