# BUBLIING S

TECHNICAL SPECIFICATIONS





# Small in size, big on solutions.

Being the smallest of all models, it's perfect for giving you full privacy for phone calls, video meetings, or other small individual tasks.

- $\stackrel{\bigcirc}{\hookrightarrow}$  Space for individual use.
- 메 Class A soundproofing.
- Guaranteed privacy and comfort.
- $\lessapprox$  Automatic ventilation and lighting.

1

#### **BUBLIING S | TECHNICAL SPECIFICATIONS**

#### **GENERAL DESCRIPTION**

**Dimensions** Exterior: 1206x1006x2245 mm / 47,48x39,61x88,39 in.

With castors:  $+52 \, \text{mm} / 2,05 \, \text{in}$ . With Bubling Fresh Air:  $+50 \, \text{mm} / 1,97 \, \text{in}$ .

Interior: 914x974x2060 mm / 35,98x38,35x81,10 in.

**Entry Height:** 86 mm / 3,39 in; **With castors:** 138 mm / 5,43 in.

Door: 2108x825 mm / 82,99x32,48 in.

Standard weight 360 kg / 794 lb.

Acoustics Class A | dB,A > 30 dB.

Guaranteed speech level reduction according to ISO 23351-1 testing

method, with one of the highest ratings in the industry.

Sound output Sound impact produced by the ventilation system.

Interior: 36 dB at head height. Exterior: 25 dB at a distance of 1 meter. Test conducted according to ISO 11201:2010.

Fan flow rate Airflow: 280.4 m<sup>3</sup>/h (2 fans).

Air is renewed, on average, every 5.6 minutes.

Airflow can be manually adjusted.

In standby mode, the system activates for 10 minutes per hour.

**Lighting** Ceiling Light: LED lighting with a color temperature of

3500K–4000K, providing up to 500 lux on the desk.

Face Light: LED lighting with a color temperature of
3500K–4000K, providing up to 500 lux on the user's face.
Lighting is automatic and can be manually adjusted.

Occupancy indicators LED sensor technology with exterior red or green light.

**Digital control** 7" touchscreen digital control panel.

**Mobility** High-resistance leveling feet adjustable from inside the booth.

BUBLIING is prepared for the installation of castors (optional). The leveling feet must be raised to move the booth and lowered

once it is in the desired position.

## MATERIALS

Exterior panels: Made of powder-coated steel, available in 10

interchangeable colors.

 $\textbf{Frame and door:} \, \textbf{Made of matte black lacquered aluminum (RAL} \,$ 

9005) with concealed pivot hinge. **Handle:** Made of textured black polymer. **Glass:** 8 mm / 0.31 in clear acoustic glass.

Interior Structure: Metal frame, wood, and recycled acoustic foam.

**Covering:** 100% polyester fabric available in 12 colors. **Flooring:** 100% polyamide carpet available in 4 colors.

Table: Birch plywood top with white, black fingerprint-resistant

thermolaminate, or wood imitation finish.

Metal support structure.

**Standard furniture Table Dimensions**: 730 x 400 x 1050 mm / 28.74 x 15.75 x 41.34 in.

**Table Height:** 730 or 1050 mm / 28.74 or 41.34 in. Maximum load for the table is 50 kg / 110.23 lbs. **Clothes hanger (1):** lacquered in textured black RAL 9005.

Furniture options Sofa: 730 x 570 x 810 mm / 28.74 x 22.44 x 31.89 in.


High stool: 400 x 400 x 580-780 mm / 15.75 x 15.75 x 22.83-30.71 in.


Backrest: 570 x 145 x 760 mm / 22.44 x 5.71 x 29.92 in.


These optional pieces are upholstered in 100% polyester fabric,


available in 12 colors.

Maximum load for the sea is 135 kg / 297.12 lbs.









#### **BUBLIING S | TECHNICAL SPECIFICATIONS**

#### **SAFETY**

products are tested and classified according to national or

international standards.

Fabrics: EN 13501-1 Adhered Class B, s1, d0.

Foams: ISO 3795. Carpet: EN 13501-1 Cfl – s1. Wood: EN 13986, Class D-s2, d0.

Seismic protection The BUBLIING can be supplied with a system that allows attachment

to the floor, available for seismic regions.

#### **ENERGY**

Charger output 1x Schuko socket – 230 V.

1x USB-C port.

Optional: USB-A port, RJ45 network socket.

Equipment power 30 W.

Standby consumption 0,74 W.

Standard consumption AC output (power socket); 100–240 VAC, 16 A, 50–60 Hz.

Electrical equipment 18 W USB-C output.

#### **EXTRA FEATURES**

Options Metal hydraulic air spring for door closer.

Invisible wireless charger integrated into the table.

**High load capacity castors.** Castors and leveling feet are adjustable from inside the

BUBLIING.

Adjustable **facial light** up to 500 lux directed at the user's face. **Bubliing Fresh Air system**, non-adjustable and noise-free.

Sofa cushion upholstered in 100% polyester fabric, available in 12 colours. Height-adjustable lift table system, from 730 to 1200 mm /  $28.74 \times 47.24$  in.

#### SPACE AND INSTALLATION

Required Space BUBLIING depth 1006 mm / 39.61 in + 100° door opening. Minimum

recommended clearance for air circulation above and on the sides 150


mm / 5.91 in.

Installation Space Installation requires 500 mm / 19.69 in of free space around the

BUBLIING.

Assembly time: 30 minutes.

Number of people: 2 people.



# **BUBLIING S | STANDARD FURNITURE**





HIGH TABLE 730x400x1050 mm. 28,74x15,75x41,34 in.



CLOTHES HANGER 1 unit.

# **BUBLIING S | OPTIONAL FURNITURE**









LOW TABLE 730x400x730 mm. 28,74x15,75x28,74 in.



**SOFA** 730x570x810 mm. 28,74x22,44x31,89 in.



HIGH STOOL 400x400x580-780 mm. 15,75x15,75x22,83-30,71 in.



BACKREST 570x145x760 mm. 22,44x5,71x29,92 in.

# **BUBLIING S | STANDARD FEATURES**



**CONNECTIVITY**1x standard Schuko socket - 230 V.
1x USB-C port.



CONTROL SCREEN
7-inch digital control.



OCCUPANCY INDICATOR
Exterior LED sensor technology.
2 units.

## **BUBLIING S | OPTIONAL FEATURES**



**CASTERS**High load capacity.
Adjustment is made from the inside.



AIR SPRING
Metal hydraulic system for the door.



WIRELESS CHARGER
Invisible charger built into the table.



FACIAL LIGHT
LED lighting 3500 K - 4000 K.
Up to 500 lux on the user's face.



**LIFTING TABLE**Height adjustable system: 730-1200 mm / 28.74x47.24 in.



SOFA CUSHION
Covered with 100% polyester fabric.
12 colors available.



BUBLIING FRESH AIR Non-adjustable system. Noise-free.



## **BUBLIING S | FINISHES**



### TABLE TOP



Due to the different monitor and printer configurations, the appearance of the finishes may vary from the actual finish. To ensure that the chosen finishes meet your expectations, please refer to physical samples or contact a BUBLIING representative.

WORK WELL, LIVE BETTER
WITH **BUBLIING S**