BUBLIING XL

TECHNICAL SPECIFICATIONS





Expandir as possibilidades, elevar as expectativas.

his model takes versatility to the next level.

It creates a serene environment for larger team meetings, offering functional equipment for presentations or strategic planning sessions.

- A space for 6 people.
- III Class A soundproofing.
- Guaranteed privacy and comfort.
- \lessapprox Automatic ventilation and lighting.
- & Designed for PRM.

1

BUBLIING XL | TECHNICAL SPECIFICATIONS

GENERAL DESCRIPTION

Dimensions Exterior: 2356x2006x2245 mm / 92,76x78,98x88,39 in.

With Bubling Fresh Air: + 50 mm / 1,97 in

Interior: 2085x1976x2114 mm / 82,09x77,80x83,23 in.

Entry Height: 23 mm / 0,91 in. Door: 2134x949 mm / 83,90x37,36 in.

Standard weight 930 kg / 2059 lb.

Acoustics Class A | dB,A > 30 dB.

Guaranteed speech level reduction according to ISO 23351-1 testing method, with one of the highest ratings in the industry.

Fan flow rate Airflow: 1121,6 m³/h (8 fans).

Air is renewed, on average, every 5.6 minutes.

Airflow can be manually adjusted.

In standby mode, the system activates for 10 minutes per hour.

Lighting Ceiling Light: LED lighting with a color temperature of

3500K–4000K, providing up to 500 lux on the desk. Lighting is automatic and can be manually adjusted.

Occupancy indicators LED sensor technology with exterior red or green light.


Digital control 7" touchscreen digital control panel.

Mobility High-resistance leveling feet adjustable from inside the booth.

BUBLIING is designed to accommodate people with reduced

mobility and wheelchair users.

Ramp with an entry height of 23 mm / 0.91 in.



MATERIALS

Exterior panels: Made of powder-coated steel, available in 10

interchangeable colors.

Frame and door: Made of matte black lacquered aluminum (RAL

9005) with concealed pivot hinge. **Handle:** Made of textured black polymer. **Glass:** 8 mm / 0.31 in clear acoustic glass.

Interior Structure: Metal frame, wood, and recycled acoustic foam.

Covering: 100% polyester fabric available in 12 colors. **Flooring:** 100% polyamide carpet available in 4 colors.

Table: Birch plywood top with white, black fingerprint-resistant

thermolaminate, or wood imitation finish.

Metal support structure.

Standard furniture Table dimensions: 1745x870x730 mm / 68,70x34,25x28,74 in.

Table Height: 730 ou 1050 mm / 28,74 ou 41,34 in. Maximum load for the table is $50 \, \text{kg}$ / $110.23 \, \text{lbs}$.


Sofa dimensions: 1720x570x810 mm / 67,72x22,44x31,89 in. Sofa upholstered in 100% polyester fabric, available in 12 colors.


Maximum load for the sea is 135 kg / 297.12 lbs. Clothes hangers (2): lacquered in textured black RAL 9005.

PRM kit This model is designed to meet the needs of people with reduced

mobility (PRM). Please refer to the PRM kit technical sheet for

additional details.





BUBLIING XL | TECHNICAL SPECIFICATIONS

SAFETY

products are tested and classified according to national or

international standards.

Fabrics: EN 13501-1 Adhered Class B, s1, d0.

Foams: ISO 3795. Carpet: EN 13501-1 Cfl – s1. Wood: EN 13986, Class D-s2, d0.

Seismic protection The BUBLIING can be supplied with a system that allows attachment

to the floor, available for seismic regions.

ENERGY

Charger output 3x Schuko sockets - 230 V.

1x USB-C port. 1x USB-A port. 1x RJ45 Network socket. Optional: HDMI input.

Equipment power 118 W.

Standby consumption 0,74 W.

Standard consumption AC output (electrical socket); 100-240 VAC, 16 A, 50-60 Hz.

Electrical equipment 65 W USB-C output.

EXTRA FEATURES

Options Metal hydraulic air spring for door closer.

Bubliing Fresh Air system, non-adjustable and noise-free.

Sofa cushion upholstered in 100% polyester fabric, available in 12 colours. Metal interior monitor stand with VESA mounting. Monitor not included.

Maximum monitor size is 13-42 inches.

Metal exterior monitor stand with VESA mounting. Monitor not included.

Maximum monitor size is 37-70 inches.

Outdoor whiteboard 1594x910 mm / 62,76x35,83 in.

SPACE AND INSTALLATION

Required Space BUBLIING depth 2006 mm / 78.98 in + Door opening of 100°.

Minimum recommended airflow space above and on the sides: 150


mm / 5.91 in.

Installation Space Installation requires 500 mm / 19.69 in of free space around the

BUBLIING.

Assembly Assembly time: 2 hours.

Number of people: 3 people.



BUBLIING XL | STANDARD FURNITURE





LOW TABLE 1745x870x730 mm. 68,70x34,25x28,74 in.



SOFA 1720x570x810 mm. 67,72x22,44x31,89 in.



CLOTHES HANGERS 2 units.

BUBLIING XL | OPTIONAL FURNITURE





HIGH TABLE. 1745x870x1050 mm. 68,70x34,25x41,34 in.

BUBLIING XL | STANDARD FEATURES



CONNECTIVITY

3x standard Schuko sockets - 230 V. 1x USB-C port. 1x USB-A port. 1x RJ45 network socket.



CONTROL SCREEN

7-inch digital control.



OCCUPANCY INDICATOR

Exterior LED sensor technology. 2 units.

BUBLIING XL | OPTIONAL FEATURES



AIR SPRING

 $\label{thm:metal-loss} \mbox{Metal hydraulic system for the door.}$



BUBLIING FRESH AIR

Non-adjustable system. Noise-free.



SOFA CUSHION

Covered with 100% polyester fabric. 12 colors available.



INDOOR MONITOR STAND

Monitor not included. Size: 13-42 inches.



OUTDOOR MONITOR STAND

Monitor not included. Size: 37-70 inches.



OUTDOOR WHITEBOARD

1040x910 mm. 40,94x35,83 in.



BUBLIING XL | FINISHES



TABLE TOP



Due to the different monitor and printer configurations, the appearance of the finishes may vary from the actual finish. To ensure that the chosen finishes meet your expectations, please refer to physical samples or contact a BUBLIING representative.

WORK WELL, LIVE BETTER
WITH **BUBLING XL**