BUBLIING L

TECHINICAL SPECIFICATIONS





All the answers, in one place.

It stands out for its versatility. It offers a quiet space to gather in small groups, with functional furniture and support materials for presentations or strategic planning.

- A space for 4 people
- III Insonorização Classe A
- Privacidade e conforto garantido
- 🥦 Ventilação e iluminação automática
- 🖒 Designed for PMR

BUBLIING L | TECHINICAL SPECIFICATIONS

GENERAL DESCRIPTION

Dimensions Exterior: 2356x1456x2245 mm / 92,76x57,32x88,39 in

With Bubling Fresh Air: Additional 50 mm / 1,97 in **Interior:** 2058x1426x2114 mm / 81,09x56,14x83,23 in

Entrance height: 23 mm / 0,91 in The door: 2134x949 mm / 83,90x37,36 in

Standard weight 740 kg / 1632 ib

Acoustic Class A | DB,A > 30 dB

Guaranteed speech level reduction according to the ISO 23351-1 testing method, with one of the best ratings in the industry.

Fan airflow: 1121,6 m³/h (8 fans)

The air is renewed, on average, every 5,6 minutes.

The airflow can be manually adjusted.

In standby mode, the system activates for 10 minutes per hour.

Lighting Ceiling light: LED lighting with a temperature of 3500 K - 4000 K,


providing up to 500 lux on the desk.

The lighting is automatic and can be manually adjusted.

Occupancy indicators LED sensor technology with red or green light indicator.

MobilityHigh-strength levelers adjustable from inside the booth.

The BUBLIING is designed for people with limited mobility and wheelchairs. Ramp with an entrance of 780 mm / 30.71 in.



MATERIALS

Exterior Exterior panels: Made of thermocoated steel, replaceable in 10

available colors.

Frame and door: Made of aluminum coated in matte black RAL

9005, with an invisible pivot hinge. **Handle:** Made of textured black polymer. **Glass:** Clear acoustic glass, 8 mm / 0.31 in.

Interior Structure: Metal frame, wood, and recycled acoustic foam.

Upholstery: 100% polyester fabric available in 12 colors. **Flooring:** 100% polyamide carpet available in 4 colors.

Table: Top and lower box made of birch plywood covered with white, fingerprint-resistant black laminate, or wood imitation

laminate.

 $\textbf{Standard furniture} \qquad \qquad \textbf{Table dimensions: } 1195 \times 830 \times 730 \text{ mm} \, / \, 47.05 \times 32.68 \times 28.74 \text{ in}$

Table height: 730 or 1050 mm / 28.74 or 41.34 in Maximum load for the table is 50 kg / 110.23 lbs

Sofa dimensions: 1173x570x810 mm / 46.18x22.44x31.89 in Sofa upholstered in 100% polyester fabric, available in 12 colors. Clothes hangers (2): coated in textured black RAL 9005.


Options PMR Retractable table: 1195x810x730 mm / 47.05x31.89x28.74 in


Retractable sofa: 1178x610x490 mm / 46.42x24.02x19,29 in Support bars (2): located on the door, inside, with a height of 850

mm / 33.46 in

Protection plates (4): for the door, inside and outside: 840x180 mm

/ 33.07x7.09 in





BUBLIING L | TECHINICAL SPECIFICATIONS

SAFETY

products are tested and classified according to national or

international standards.

Fabrics: EN 13501-1 Adhered Class B, s1, d0

Foams: ISO 3795 Carpet: EN 13501-1 Cfl – s1 Wood: EN 13986, Class D-s2, d0

Earthquake resistance The BUBLING can be supplied with a system that allows fixation to the

floor, available for seismic regions.

ENERGY

Electrical equipment 2x Schuko sockets - 230 V

1x USB-C port 1x USB-A port

Optional: RJ45 network socket; HDMI port.

Standard consumption 93 W

Standby consumption 0,74 W

Equipment power AC output (electrical socket); 100-240 VAC, 16 A, 50-60 Hz.

Charger output USB-C output 18 W

EXTRA FEATURES

Options | 7-inch manual control screen.

| Metal hydraulic air spring for door closure.

| Bubliing Fresh Air system, non-adjustable and noise-free.

Internal metal monitor support with VESA mounting. Monitor not included. Maximum

monitor size is 32/42 inches.

 $|\:\textbf{Exterior whiteboard}\:1040x910\:mm\:/\:40.94x35.83\:in$

SPACE AND INSTALLATION

Required space BUBLIING depth: 1456 mm / 57.32 in + Door opening of 100°.

Minimum recommended space for air circulation above and on the


sides: 150 mm / 5.91 in.

 $\textbf{Installation space} \qquad \qquad \textbf{The installation requires 500 mm / 19.69 in of free space around the} \\$


BUBLING.

Assembly Assembly time: 2 hours

Number of people: 3 people



BUBLIING L | STANDARD FURNITURE





LOW TABLE 1195x830x730 mm 47,05x32,68x28,74 in



SOFAS 1173x570x810 mm 46,18x22,44x31,89 in



CLOTHES HANGERS 2 units

BUBLIING L | OPTIONAL FURNITURE





HIGH TABLE 1195x830x1050 mm 47,05x32,68x41,34 in

BUBLIING L | OPTIONAL PMR



RETRACTABLE TABLE AND SOFAS Table: 1195x810x730 mm /

47,05x31,89x28,74 in. Sofas: 1178x610x490 mm / 46,42x24,02x19,29 in.



SUPPORT BARS

1 unit inside each door, at a height of 850 mm / 33.46 in.



PROTECTION PLATES

Inside and outside of the doors. 840x180 mm / 33.07x7.09 in.

BUBLIING L | STANDARD FEATURES



CONNECTIVITY

2x standard Schuko sockets - 230 V

1x USB-C port

1x USB-A port



DIMMER SWITCHIntensity regulator for lighting and ventilation.



OCCUPANCY INDICATOR
Tecnologia a sensore LED per esterni.
2 unità.

BUBLIING L | OPTIONAL FEATURES



AIR SPRINGMetal hydraulic for door.



BUBLIING FRESH AIR Non-adjustable system. Noise-free.



CONTROL SCREEN
7-inch manual control.



SOFA CUSHIONCovered with 100% polyester fabric. 12 colors available.



INTERNAL MONITOR SUPPORT Monitor not included. Maximum size: 32/42 inches.



SUPORTE MONITOR EXTERIOR Monitor not included. Maximum size: 32/42 inches.



EXTERNAL WHITE BOARD 1040x910 mm 40,94x35,83 in



BUBLIING L | FINISHES



TABLETOP



Due to the different configurations of monitors and printers, the appearance of the finishes may vary from the actual finish. To ensure that the chosen finishes meet your expectations, please refer to physical samples or contact a BUBLIING representative.

WORK WELL, LIVE BETTER
WITH **BUBLIING L**